DuPont Page 1

Material Safety Data Sheet

AHG Salution Tohydroxamyl Chloride

L0800761 Revised 21-MAY-2011 Printed 11-JUN-2012

Business and Sites

05: 7351

CHEMICAL PRODUCT/COMPANY IDENTIFICATION

Material Identification

DuPont Registry Number: DP209-33-Q
PNOH Indicator: N
GOrporate Roll-up Ind.: N
SR08 Proposal Ind.: N

Product Type: I Status Indicator: F

Tradenames and Synonyms

Liquid In 7022 Reactor (FAA 7022-1)
Liquid In 7022 Cooler
Liquid In 7022 Cooler
Liquid In 08P Cells
Acetohydroxyamylchloride

Company Identification

MANUFACTURER/DISTRIBUTOR

OUPont

12501 Strang Road
P.O. Box 347
La Porte, TX 77572-8347

PHOME NUMBERS
Product Information: 1-806-441-7515
Transport Emergency: 1-800-441-3637

COMPOSITION/INFORMATION ON INSREDIENTS

Components

Material CAS Number %
Acetaldehyde 75-07-0 <10
Hater 7732-18-5 76

\* Disclosure as a toxic chemical is required under Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1988 and 40 CFR part 372.

L0000761

OuPont Material Safety Data Sheet Page 2

HAZARDS IDENTIFICATION

Potential Health Effects

Skin contact may cause skin burns or ulceration. Acotaldehyde has been infrequently associated with skin sensitization in humans.

Eye contact may cause eye corrosion with corneal or conjunctival ulceration.

Inhalation may cause irritation of the upper respiratory passages, with coughing and discomfort; nonspecific discomfort, such as nausea, headache, or meakness. Higher exposures may lead to corrosion of mucosal surfaces with temporary lung irritation effects with cough, discomfort, difficulty breathing, or shortness of breath; may cause pulmonary edema (body fluid in the lungs) with cough, wheezing, abnormal lung sounds, possibly progressing to sowere shortness of breath and bluish discoloration of the skin. Symptoms may be delayed. Prompt medical attention is required; dental erosions; and fatality from gross overexposure.

Ingestion may cause severe burns of the mouth, throat, esophagus and stomach with burning pain of the mouth, throat, chest and abdoman. Vomiting and diarchea of dark blood may occur and penetration of the esophagus or stomach.

A study of chemical workers showed no association between hydrogen chloride exposure and lung cancer.

Exposure to large amounts of acetaldehyde may cause the "acetaldehyde syndrome". At first, blood pressure rises; the face, then the rest of the body become hot and flushed; a throbbing headache may develop. Sweating, thirst, dizziness and vomiting can occur. Then, blood pressure falls, resulting in weakness, dizziness, or fainting.

Gertain oral anti-diabetic drugs and antibiotics (cephalosporins) reduce the body's ability to eliminate acetaldehyde. Individuals taking these drugs or who have preexisting diseases of the lungs or liver may have increased susceptibility to the toxicity of excessive exposures.

Carcinogenicity Information

The following components are listed by IARC, HTP, OSHA or ACGIH as carcinogens.

Material Acetaldehyde IARG NTP OSHA ACGIH

L0000761

DuPont Material Safety Data Sheet

FIRST AID MEASURES

First Aid

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician.

In case of contact, immediately flush skin with planty of water for at least 15 minutes, while removing contaminated clothing and shoes. Call a physician. Wash contaminated clothing before reuse.

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Call a physician.

If swallowed, do not induce vomiting. Immediately give 2 glasses of water. Never give anything by mouth to an unconscious person. Call a physician.

Notes to Physicians

Activated charcoal mixturs may be administered. To propare activated charcoal mixture, suspend S0 grams activated charcoal in 400 mL water and mix thoroughly. Administer 5 mL/kg, or 350 mL for an average adult.

FIRE FIGHTING MEASURES
Flammable Properties

Will detonate if suitably primed, with severe impact, or by heat or flame.  $\dot{\ }$ 

Extinguishing Media

Water Fog.

Fire Fighting Instructions

Evacuate personnel to a safe area. Wear self-contained breathing apparatus. Wear full protective equipment. Flood with water.

L0000761	DuPont Material Safety Data Sheet	Page
ACCIDENTAL RELEASE ME	***************************************	
sections before pr	FIGHTING MEASURES and HANDLING occeding with clean-up. Use app E EQUIPMENT during clean-up.	PERSONNEL) propriate
Evacuate personnel breathing apparatu	, thoroughly ventilate area, use s.	self-contained
Initial Containment		
low areas.	nt material from entering sewers	
HANDLING AND STORAGE	• • • • • • • • • • • • • • • • • • • •	
Handling (Personnel)		
Do not breathe vapo clothing. Wash the use. Discard shoes	or or mist. Do not get in eyes, proughly after handling. Wash c a if contaminated.	on skin, or on lothing after
Handling (Physical Asp	nects)	
Keep away from heat	t, sparks and flames.	
Storage		
Store in a cool pla	ice. Keep container tightly clo	sed.
EXPOSURE CONTROLS/PERS		
Engineering Controls		•••••••
Use only with adequ	ate ventilation. Keep containe	tightly clased.
Personal Protective Eq	uipment	
Eye/Face Respirator Additional	: Coverall chemical splash ; Air supplied respirator. : Chemical suit. Protectii Cuffs and sleeves of suit taged closed.	/e footwear.
Protective Gloves	: Neoprene.	
Exposure Guidelines		

L0000761 DuPont Haterial Safety Oata Sheet

Applicable Exposure Limits
Hydrochloric Acid
PEL (OSHA) : S ppm, 7 mg/m3, Ceiling
TLY (ACGIH) : Ceiling 2 ppm, A4
AEL \* (DuPont) : S ppm, 15 minute THA

Acataldehyde
PEL (OSHA) : Ceiling 25 ppm, 45 mg/m3, 8 Hr. TMA
TLY (ACGIH) : Ceiling 25 ppm, 45 mg/m3, A3
Notice of Intended Changes (2011)
Ceiling 28 ppm, A2
AEL \* (DuPont) : Ceiling 28 ppm, A5 mg/m3, A3
Notice of Intended Changes (2011)
Ceiling 28 ppm, A5 mg/m3, A3
Actice of Intended Changes (2011)
Ceiling 28 ppm, A5 mg/m3, A3
Notice of Intended Changes (2011)
Ceiling 28 ppm, A7
AEL is OuPont's Acceptable Exposure Limit. Where governmentally imposed occupational exposure Iimits which are Lower than the AEL are in effect, such limits shall take procedence.

PHYSICAL AND CHEMICAL PROPERTIES

Physical Oata

Vapor Pressure : 20 mm Hg @ 61 C (142 F)
Vapor Density : 3.2 (Air=1)
Melting Point : -15 to -22 C (5 to -8 F)
Odor : Sharp and irritating
Form : Liquid
Color : Greenish blue to purple
Specific Gravity : 1.078

STABILITY AND REACTIVITY

Chemical Stability

Unstable With heat. Unstable with shock.

Overchlorination of AAO results in the formation of dichiloro-nitroso ethane, or DCNE. DCNE has limited solubility in ANO and precipitates as a separate heavy phase. Heavy phase OCNE extreat AHC and other organics forming a material called "blue oil". In calorimetry tests, "blue oil" decomposes violently. There are two exotherms, one is at or above 31 C (88 F), and a second at about 76 C (169 F).

Incompatible with basic solutions Chlorine in excess of 15% forms 1-chloro-1-nitrosoethane.

Decomposition

Decomposes with heat.

L0000781

OuPont Material Safety Data Sheet

Page 6

## (STABILITY AND REACTIVITY - Continued)

Decomposition temperature: 31 G (88 f)

Hazardous gases/vapors produced are 1,1-dichloro-1-nitrosoethane, acatonitrile-oxide and acetohydroxamyl chloride.

#### Polymerization

Polymerization will not occur.

TOXICOLOGICAL INFORMATION

Animal Data

# ACETOHYOROXAMIZE CHLORIDE

Inhalation 1 hour ALC: 40-60 ppm in rats Oral ALD: 90 mg/kg in rats

The compound is corrosive in the eye. Toxic effects described in animals from short exposures by inhalation, ingestion, or skin contact include respiratory and pulmonary effects, and nonspecific effects such as weight loss and irritation.

## HYOROCHLORIC ACID

Inhalation 1 hour LC50: 2810 ppm in rats Oral LD50: 900 mg/kg in rabbits

The compound is corrosive to skin and eyes, but is not a skin sensitizer in animals. The effects in animals from single inhalation exposures include respiratory irritation, corneal opacity, and corrosion of mucosal surfaces. Repeated and long-term exposures produced changes in the nasal cavity with necrosis, irregular breathing, thickening or changes in mucosal lining, and reduced weight gain. Long-term exposures also produced decreased liver weights. A single oral exposure produced gastric mucosal damage. Administration of repeated oral doses produced decreased body weight gain, mortalities and nonspecific changes. Long term dosing resulted in decreased relative and absolute spleen weights.

Tests in animals demonstrate no carcinogenic activity. Adequate tests in animals for developmental or reproductive effects have not been performed.

The compound does not produce genetic damage in bacterial cell cultures, does not generally produce genetic damage in mammalian cell cultures.

ACETALDEHYDE

DuPont Material Safety Data Sheet

Page

### (TOXICOLOGICAL INFORMATION - Continued)

Inhalation 4 hour LC50: 13,300 ppm in rats Oral LO50: 1,930 mg/kg in rats

Acataldahyde is a mild skin irritant and is a severe eye

In animals, effects from brief high inhalation exposures to Acetaldehyde include excitability, rapid breathing, increased blood pressure and heart rate, and anesthetic effects. Repeated exposures caused respiratory irritation, damage to the lining of the respiratory tract, altered lung function, changes in liver and kidney function, and altered hematology. Long term exposures caused decreased growth and inflammation, abnormal tissue growth, and cell death (necrosis) in the upper respiratory tract. In animals, effects of repeated oral doses include irritation of the gastrointestinal tract and altered liver function.

Acetaldehyde is carcinogenic in rats and hamsters, producing tweers of the mose and throat.  $\label{eq:constraint} % \begin{array}{c} \frac{1}{2} \left( \frac{1}{2} - \frac{1}{2} \right) & \frac{1}{2} \left( \frac{1}{2} - \frac{1}{2} \right) \\ \frac{1}{2} \left( \frac{1}{2} - \frac{1}{2} - \frac{1}{2} \right) & \frac{1}{2} \left( \frac{1}{2} - \frac{1}{2} - \frac{1}{2} \right) \\ \frac{1}{2} \left( \frac{1}{2} - \frac{1}{$ 

Acstaldehyde has been tested for its ability to cause developmental toxicity. Most tests have used large amounts given by injection. The results showed that the compound harms the unborn fetus, but the risk to humans from occupational exposure cannot be accurately predicted because of the large doses and route of exposure used.

There are reports indicting that Acetaldehyde produced genetic damage in some bacterial cell cultures, however the majority of reported tests are negative. This compound does produce genetic damage in mammalian cell cultures as well as in tests on animals.

ECGLOGICAL INFORMATION

Ecotoxicological Information

Aquatic Toxicity

96 hour LC50, mosquito fish: 282 mg/L for Hydrochloric Acid 96 hour LC50, fathead minnow: 79 mg/L for Acetic ACid

DISPOSAL CONSIDERATIONS

Waste Disposal

On not flush to surface water or sanitary sewer system.

Recover nonusable free liquid and/or contaminated water, and dispose of in an approved and permitted biological treatment system or an approved and permitted deepwell.

L0000761 OuPont Material Safety Data Sheet OTHER INFORMATION References: Haskell Toxicity Information Summary #598 for Acetohydroxamyl Chloride, #88 for Hydrochloric Acid and #1294 for Acetaldehyde. Latest MSOS revision date: 99/07/18. The data in this Material Safety Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process.

# Indicates updated section.

End of MSOS